

DISPARLON

October 2021

DISPARLON APA-100

(Surface control agent)

DISPARLON APA-100 is an acrylic polymer type surface control agent which prevents overcoatability and intercoat adhesion issues. **DISPARLON APA-100** is also effective to prevent Amine Blushing of epoxy systems.

ADVANTAGES

- Prevent overcoatability and intercoat adhesion issues.
- Prevent Amine Blushing.
- Silicone free.
- Aromatic free.

APPLICATIONS

DISPARLON APA-100 can be used a wide range of coating systems and is especially recommended for amine curing epoxy coatings for Marine and Protective coatings.

INCORPORATION

Additive levels : 0.3 ~1.0 % by weight on total formulation. *

*The optimal level, however, should be determined by your laboratory tests.

Method : While this additive can be added at each production stage, post-addition at a final production stage stirring with a dissolver is recommended.

TYPICAL PROPERTIES

Appearance : Clear to light yellow liquid

Active component : 50 % by wt.

Solvent : n-Butyl acetate



Kusumoto Chemicals, Ltd.

11-13, UCHIKANDA 1-CHOME, CHIYODA-KU, TOKYO JAPAN

(TEL) 81-3-3292-8685 (FAX) 81-3-3295-6079

The information on use is based on data which are believed reliable, but any recommendation or suggestion made are without guarantee or warranty, since the conditions of use are outside our control. All products are sold on the conditions that purchasers shall make their own tests to determine the suitability of such products for their purpose and that all risks are assumed by user. We disclaim any responsibility for damages resulting from careless or improper handling or use. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license. See SDS for safety handling before to use.

© 2014-2021 All Rights Reserved By Kusumoto Chemicals, Ltd.