

Additives for coatings and printing inks
DISPARLON®

May 2024

DISPARLON® BAL-D329

(Biomass-derived wetting/dispersing and anti-settling agent)

DISPARLON® BAL-D329 is a biomass-derived wetting/dispersing and anti-settling agent and is highly effective for dispersing inorganic pigments such as titanium oxide. DISPARLON® BAL-D329 forms a weak structure by agglomerating with pigments and fillers in a system, improves dispersibility, and provides anti-settling and anti-floating properties.

ADVANTAGES

- Environmentally friendly: high biobased content
- Improves pigment wetting and dispersing properties
- Stabilizes dispersed pigments: prevents reagglomeration and provides anti-settling, anti-flooding, and anti-floating properties

APPLICATIONS

DISPARLON® BAL-D329 can be used for a wide range of inorganic pigments and fillers in non-aqueous systems such as solvent-borne coatings and printing inks.

INCORPORATION

- Additive levels : 1 – 3 wt% for inorganic pigments.
The optimal additive level should be determined under an actual use condition.
- Method : Addition at a grinding/dispersing stage is recommended.

TYPICAL PROPERTIES

(The following figures are typical properties, not to be used for specification.)

Appearance	Yellow to amber liquid
Active component	100 %
Biobased content	100 %
Density (20 deg.C)	0.93 g/cm ³
Acid value	143

STORAGE

- Precipitation or solidification may occur at low temperature.
In this case, heat at approx. 50 deg.C for more than one day and stir well before use.



Kusumoto Chemicals, Ltd.

11-13, UCHIKANDA 1-CHOME, CHIYODA-KU, TOKYO JAPAN
(TEL) 81-3-3292-8685 (FAX) 81-3-3295-6079

The information on use is based on data which are believed reliable, but any recommendation or suggestion made are without guarantee or warranty, since the conditions of use are outside our control. All products are sold on the conditions that purchasers shall make their own tests to determine the suitability of such products for their purpose and that all risks are assumed by user. We disclaim any responsibility for damages resulting from careless or improper handling or use. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license. See SDS for safety handling before to use.

© 2024 All Rights Reserved By Kusumoto Chemicals, Ltd.