

*Additives for coatings and printing inks*  
**DISPARLON<sup>®</sup>**

December 2023

**DISPARLON<sup>®</sup> VP-D03**  
(Filler wetting / dispersing agent)

**DISPARLON<sup>®</sup> VP-D03** is a solvent-free wetting / dispersing agent composed of polyether phosphate and polyamine, and is suitable for solvent-free systems. **DISPARLON<sup>®</sup> VP-D03** is highly effective for wetting / dispersing fillers and reduces the viscosity of high filler loading systems.

**ADVANTAGES**

- Effective for a wide range of fillers
- Excellent filler wetting, dispersing, and viscosity reduction properties
- Solvent-free (100% Active)

**APPLICATIONS**

**DISPARLON<sup>®</sup> VP-D03** is recommended for solvent-free systems such as Unsaturated polyesters, Epoxies and 2K urethanes.

**INCORPORATION**

Additive levels : 1 – 20 wt% for fillers  
Method : Addition at a filler mixing stage is recommended.

**TYPICAL PROPERTIES**

(The following figures are typical properties, not to be used for specification.)

Appearance	Light yellow to amber liquid
Non-volatile matter	95.0 % or more
Acid value	14
Amine value	20



*Kusumoto Chemicals, Ltd.*

11-13, UCHIKANDA 1-CHOME, CHIYODA-KU, TOKYO JAPAN  
(TEL) 81-3-3292-8685 (FAX) 81-3-3295-6079

The information on use is based on data which are believed reliable, but any recommendation or suggestion made are without guarantee or warranty, since the conditions of use are outside our control. All products are sold on the conditions that purchasers shall make their own tests to determine the suitability of such products for their purpose and that all risks are assumed by user. We disclaim any responsibility for damages resulting from careless or improper handling or use. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license. See SDS for safety handling before to use.

© 2023 All Rights Reserved By Kusumoto Chemicals, Ltd.