DISPARLON® P-467

Defoamer

TECHNICAL DATA SHEET
Issued on 5 November 2026

DISPARLON® P-467 is a vinyl polymer-based defoamer. DISPARLON® P-467 provides rapid foam knockdown and long-lasting defoaming performance in high-viscosity systems, including paints, where conventional defoamers are often less effective.

TYPICAL PROPERTIES

The following figures are typical properties, not to be used for specification.

Appearance	Clear to light yellow liquid
Non-volatile matter	80 wt%
Solvent	Isoparaffin
Density (20 ℃)	0.828 g/cm^3
Viscosity (20 ℃)	470 mPa·s

ADVANTAGES

- Excellent defoaming effects.
- Prevents pinholes and craters.
- Promotes air release.
- Silicone-free.

APPLICATION

DISPARLON® P-467 is recommended for floor coatings, heavy-duty coatings, architectural coatings, and waterproofing coatings.

INCORPORATION

Addition levels

0.2–1.0 wt% on total formulation.
The optimal additive level should be determined under actual use conditions.

Method

Post-addition at the final production stage with a dissolver is recommended.

A higher dosage may be required when the product is added during the premix stage.

Kusumoto Chemicals, Ltd.
Kusumoto Bldg. 1-11-13 Uchikanda Chiyoda-ku Tokyo,
101-0047 Japan
TEL +81-3-3292-8685
https://www.kusumoto.co.jp/en/

The information provided herein is based on data believed to be reliable, but any recommendations or suggestions made are without guarantee or warranty, since the conditions of use are outside our control. All products are sold on the condition that purchasers shall make their own tests to determine the suitability of such products for their purpose and that all risks are assumed by the user. We disclaim any responsibility for damages resulting from careless or improper handling or use. Nothing herein is to be taken as permission, inducement, or recommendation to practice any patented invention without a license. Please refer to the SDS for safe handling before use.
© 2018-2026 Reserved By Kusumoto Chemicals, Ltd.