



DISPARLON[®] SPD-202SS

Wetting/Dispersing agent

TECHNICAL DATA SHEET

Issued on 13 July 2026

DISPARLON[®] SPD-202SS is a pigment wetting/dispersing agent composed of an amine salt of a polyester acid amide. DISPARLON[®] SPD-202SS wets and deflocculates pigments, reduces viscosity, and improves color strength, gloss, hiding power, and DOI. DISPARLON[®] SPD-202SS is especially effective for organic pigments.

TYPICAL PROPERTIES

The following figures are typical properties, not to be used for specification.

Appearance	Light yellow to amber liquid
Active matter	30 wt%
Acid value (mgKOH/g)	8
Amine value (mgKOH/g)	4
Solvent	Xylene / 2-phenoxyethanol

ADVANTAGES

- Excellent pigment wetting and dispersing
- Reduces viscosity
- Reduces grinding time
- Improves color strength, gloss, hiding power, and DOI

APPLICATION

DISPARLON[®] SPD-202SS is especially effective for dispersing organic pigments.

DISPARLON[®] SPD-202SS can be used for various coating systems such as industrial coatings, plastic coatings, and various gravure printing inks.

INCORPORATION

Addition levels

60–150 wt% for organic pigments

15–150 wt% for carbon black

3–30 wt% for inorganic pigments

Method

Addition during the grinding/dispersing stage is recommended. The optimal additive level should be determined under actual use conditions.

STORAGE

Store at 15–35°C. Precipitation or solidification may occur at low temperatures. In this case, heat at 40–50°C for 1–3 days and stir well before use.



Kusumoto Chemicals, Ltd.

Kusumoto Bldg. 1-11-13 Uchikanda Chiyoda-ku Tokyo,
101-0047 Japan

TEL +81-3-3292-8685

<https://www.kusumoto.co.jp/en/>

The information provided herein is based on data believed to be reliable, but any recommendations or suggestions made are without guarantee or warranty, since the conditions of use are outside our control. All products are sold on the condition that purchasers shall make their own tests to determine the suitability of such products for their purpose and that all risks are assumed by the user. We disclaim any responsibility for damages resulting from careless or improper handling or use. Nothing herein is to be taken as permission, inducement, or recommendation to practice any patented invention without a license. Please refer to the SDS for safe handling before use.
© 2013–2026 All Rights Reserved By Kusumoto Chemicals, Ltd.