

December 2020

DISPARLON SPL-85

(Leveling agent)

DISPARLON SPL-85 is a leveling agent based on an acrylic polymer designed specifically for high polar paint system, and it does not have the effect on haze and turbidity.

ADVANTAGES

- Improve leveling and prevent pinholes.
- Have little affect on physical properties of the film such as recoatability.
- Excellent dispersibility allows post addition.

APPLICATIONS

DISPARLON SPL-85 can be used in almost all type of solvent based systems and it especially recommended for high polar systems, particularly for Acryl/Urethane (2K).

INCORPORATION

Additive level : 0.1 ~0.5 % by weight to total formulation.*

*The optimal level, however, should be determined by your laboratory tests.

Method : While this additive can be added at each production stage, post-addition at a final production stage stirring with a dissolver is recommended.

TYPICAL PROPERTIES

AppearanceColorless to light yellow liquid

Non-volatile matter 50 % by wt.

Density 0.94 g/cm³

Solvent Solvent naphtha



Kusumoto Chemicals, Ltd.

11-13, UCHIKANDA 1-CHOME, CHIYODA-KU, TOKYO JAPAN

(TEL) 81-3-3292-8685 (FAX) 81-3-3295-6079

The information on use is based on data which are believed reliable, but any recommendation or suggestion made are without guarantee or warranty, since the conditions of use are outside our control. All products are sold on the conditions that purchasers shall make their own tests to determine the suitability of such products for their purpose and that all risks are assumed by user. We disclaim any responsibility for damages resulting from careless or improper handling or use. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license. See SDS for safety handling before to use.

© 2010-2020 All Rights Reserved By Kusumoto Chemicals, Ltd.