



DISPARLON® VP-D03

Filler Wetting/Dispersing Agent

TECHNICAL DATA SHEET

Issued on 2 October 2026

DISPARLON® VP-D03 is a solvent-free wetting and dispersing agent based on polyether phosphate and polyamine, and is suitable for solvent-free systems. DISPARLON® VP-D03 is highly effective for wetting and dispersing fillers, and reduces the viscosity of high-filler-loading systems.

TYPICAL PROPERTIES

The following figures are typical properties, not to be used for specification.

Appearance	Light yellow to amber liquid
Non-volatile matter	95.0 % or more
Acid value (mgKOH/g)	14
Amine value (mgKOH/g)	20

ADVANTAGES

- Effective for a wide range of fillers
- Excellent filler wetting, dispersing, and viscosity reduction performances
- Solvent-free (100 % Active)

APPLICATION

DISPARLON® VP-D03 is recommended for solvent-free systems such as Unsaturated polyesters, Epoxies and 2K urethanes.

INCORPORATION

Addition levels

1–20 wt% for fillers

Method

Addition during the filler mixing stage is recommended.



Kusumoto Chemicals, Ltd.

Kusumoto Bldg. 1-11-13 Uchikanda Chiyoda-ku Tokyo,
101-0047 Japan
TEL +81-3-3292-8685

<https://www.kusumoto.co.jp/en/>

The information provided herein is based on data believed to be reliable, but any recommendations or suggestions made are without guarantee or warranty, since the conditions of use are outside our control. All products are sold on the condition that purchasers shall make their own tests to determine the suitability of such products for their purpose and that all risks are assumed by the user. We disclaim any responsibility for damages resulting from careless or improper handling or use. Nothing herein is to be taken as permission, inducement, or recommendation to practice any patented invention without a license. Please refer to the SDS for safe handling before use.
© 2023–2026 All Rights Reserved By Kusumoto Chemicals, Ltd.