

Additives for coatings and printing inks
DISPARLON[®]

IT-5072E
Dec. 02, 2013

DISPARLON[®] A603-20X
(Anti-Sagging/Anti-Settling agent)

DISPARLON A603-20X is an alcohol free thixotropic agent developed for isocyanate cured paint systems. Being pre-activated, **A603-20X** can perform as well as 6900-20X just incorporated in the millbase. **A603-20X** is supplied in a paste form.

ADVANTAGES

- Alcohol free, no reaction with isocyanate.
- Strong anti-sagging/settling
- Non-seeding
- No affect on the pot-life.

APPLICATIONS

DISPARLON A603-20X is recommended for isocyanate cured systems such as Polyurethane, Acrylic/Urethane, Tar/Urethane and Epoxy/Urethane Systems.

*Don't use in the oil based systems, such as Alkyd/Melamine and other Alkyd systems.

INCORPORATION

Additive level : 1.0 ~ 5.0% by weight of total formulation.
Method : Disperse **A603-20X** sufficiently in the millbase using a sand grind mill or a high-speed dissolver.

TYPICAL PROPERTIES

Appearance : White to light yellow paste
Non-volatile matter : 20% by wt.
Solvent : Xylene



Kusumoto Chemicals, Ltd.

11-13, UCHIKANDA 1-CHOME, CHIYODA-KU, TOKYO JAPAN

(TEL) 81-3-3292-8685 (FAX) 81-3-3295-6079