

*Additives for coatings and printing inks*  
**DISPARLON<sup>®</sup>**

Oct. 17, 2013

**DISPARLON<sup>®</sup> AQ-530S**  
(Defoaming/Anti-popping agents for water-based systems)

**DISPARLON AQ-530S** is a defoaming/anti-popping agent based on blend of vinyl polymer and hydrocarbons for water borne systems, designed to disperse uniformly in the paint. There is effective not only to prevent popping and forms by reducing entrapment of air into the paint, but also to prevent foaming during production process.

**APPLICATIONS**

**DISPARLON AQ-530S** is recommended for water-borne baking systems including Alkyd/Melamine, Acrylic/Melamine and Polyester/Melamine systems.

**INCORPORATION**

Additive level : 1.5 ~2.5 % by weight on total formulation.  
Method : Post-addition on high speed dissolver is recommended.

**TYPICAL PROPERTIES**

Appearance : Colorless to light yellow liquid  
Non-volatile matter : 10 % by wt.  
Density : 0.787 g/cm<sup>3</sup>  
Solvent : Naphtha (petroleum), heavy alkylate / Solvent naphtha (petroleum), light arom.



*Kusumoto Chemicals, Ltd.*

11-13, UCHIKANDA 1-CHOME, CHIYODA-KU, TOKYO JAPAN

(TEL) 81-3-3292-8685 (FAX) 81-3-3295-6079