

*Additives for coatings and printing inks*  
**DISPARLON<sup>®</sup>**

Sep. 08, 2014

**DISPARLON<sup>®</sup> LCN-400**

(Leveling / Flow agent)

**DISPARLON LCN-400** is silicone-free, non-ionic high molecular weight surface active agents. This is 50% solids, chemically stable and have excellent dispersibility in a wide range of paint systems. This product is utilized in the advanced paint technologies including high-solids coatings and UV cured systems as surface modifiers. Especially effective in baking systems.

**ADVANTAGES**

- Improve leveling and prevent pinholes.
- Improve film gloss by promoting pigment wetting, resulting in good dispersion.
- Act as defoamer.
- Have little affect on physical properties of the film such as recoatability.
- Excellent dispersibility allows post addition.

**APPLICATIONS**

**LCN-400** can be used in almost all type of baking high-solids coatings, thermosetting, UV curing systems, non-solvent coatings as well as conventional baking solvent based coatings and Unsaturated polyester coatings, particularly high-solids Polyester / melamine and Acrylic melamine coatings for automotive and coil industries.

**INCORPORATION**

Additive level : 0.2 ~1.5% by weight on total formulation.  
Method : Post-addition on high speed dissolver is recommended.

**TYPICAL PROPERTIES**

Appearance : Colorless to light yellow liquid  
Non-volatile matter : 50% by weight  
Density : 0.96g/cm<sup>3</sup>(at 20°C)  
Solvent : Butyl acetate



*Kusumoto Chemicals, Ltd.*

11-13, UCHIKANDA 1-CHOME, CHIYODA-KU, TOKYO JAPAN

(TEL) 81-3-3292-8685 (FAX) 81-3-3295-6079