

Additives for coatings and printing inks
DISPARLON[®]

Feb. 18, 2015

DISPARLON[®] SPL-92
(Slipping/Leveling agent)

DISPARLON SPL-92 is silicone based slip/leveling agent. **DISPARLON SPL-92** has excellent compatibility to coatings without haze and improves slipping, scratch resistance, anti-blocking properties. It also prevents cratering, cissing and pin-hole that come from contamination taking full advantage of excellent leveling property.

ADVANTAGES

- Good leveling & DOI.
- Prevent crater & fish eye.
- Good dispersibility and stability on ageing in paint systems.

APPLICATIONS

DISPARLON SPL-92 can be used for all solvent based systems and it is especially recommended for Wood, Architectural, PCM and industrial top coatings such as Alkyd melamine, Acrylic melamine, Acrylic urethane.

INCORPORATION

Recommended levels : 0.1 ~ 1.0% by weight on total formulation.

Method : Post addition on High speed dissolver is recommended.

TYPICAL PROPERTIES

Appearance : Colorless to light yellow liquid
Non-volatile : 10% by weight
Density : 0.906 g/cm³
Solvent : Solvent naphtha / 2-phenoxyethanol



Kusumoto Chemicals, Ltd.

11-13, UCHIKANDA 1-CHOME, CHIYODA-KU, TOKYO JAPAN

(TEL) 81-3-3292-8685 (FAX) 81-3-3295-6079