

*Additives for coatings and printing inks*  
**DISPARLON<sup>®</sup>**

May 2013

**DISPARLON<sup>®</sup> SPL-93**  
(Slipping/Leveling agent)

**DISPARLON SPL-93** is a silicone based slip/leveling agent. **DISPARLON SPL-93** has excellent compatibility to coatings without haze and improves slipping, scratch resistance, anti-blocking properties. It also prevents cratering, cissing and pin-hole that come from contamination taking full advantage of excellent leveling property.

**ADVANTAGES**

- Good leveling & DOI.
- Prevent crater & fish eye.
- Good dispersibility and stability on ageing in paint systems.

**APPLICATIONS**

**DISPARLON SPL-93** can be used for all solvent based systems and it is especially recommended for Wood, Architectural and industrial top coatings such as Alkyd melamine, Acrylic melamine, Acrylic urethane.

**INCORPORATION**

Recommended levels : 0.2 ~ 2.0 % by weight on total formulation.  
Method : Post addition on High speed dissolver is recommended.

**TYPICAL PROPERTIES**

|                    |                                  |
|--------------------|----------------------------------|
| Appearance .....   | Colorless to light yellow liquid |
| Non-volatile ..... | 15 % by wt.                      |
| Density .....      | 0.89 g/cm <sup>3</sup>           |
| Solvent .....      | Xylene                           |



*Kusumoto Chemicals, Ltd.*

11-13, UCHIKANDA 1-CHOME, CHIYODA-KU, TOKYO JAPAN

(TEL) 81-3-3292-8685 (FAX) 81-3-3295-6079