

Additives for coatings and printing inks
DISPARLON[®]

Oct. 2012

DISPARLON[®] AQ-7503 & AQ-7533

(Universal defoamer for water-based systems)

DISPARLON AQ-7503 and AQ-7533 are silicone-free defoaming/anti-popping agents for water-based systems, composed of vinyl polymer, surfactant, hydrocarbon and higher alcohol. AQ-7503 and AQ-7533 are effective to prevent foaming during production process, reduce air-entrapment by spray application, prevent popping and improve film thickness without popping.

ADVANTAGE

- Defoaming property.
- Anti-popping property.
- Silicone-free.

APPLICATIONS

DISPARLON AQ-7503 and AQ-7533 can be used in various water-based systems. **AQ-7503 and AQ-7533** are especially suitable for baking systems such as Acrylic/Melamine and Alkyd/Melamine.

INCORPORATION

Addition level : 1.0 ~3.0 % by weight on total formulation.

Method : Post-addition is recommended.

TYPICAL PROPERTIES

	AQ-7503	AQ-7533
Appearance	Light yellow to yellow liquid	Colorless to light yellow liquid
Component	Vinyl polymer/Surfactant	
Solvent	Hydrocarbon/2-Ethylhexyl alcohol	



Kusumoto Chemicals, Ltd.

11-13, UCHIKANDA 1-CHOME, CHIYODA-KU, TOKYO JAPAN

(TEL) 81-3-3292-8685 (FAX) 81-3-3295-6079