Additives for coatings and printing inks

$DISPARLON^{\circ}$

Sep. 09, 2013

DISPARLON® JXL-621

(Slipping/Leveling agent)

DISPARLON JXL-621 is a silicone based slip/leveling agent. **DISPARLON JXL-621** has excellent compatibility to coatings without haze and improves slipping, scratch resistance, anti-blocking properties. It also prevents cratering, cissing and pin-hole that come from contamination taking full advantage of excellent leveling property.

ADVANTAGES

- Good leveling & DOI.
- Prevent crater & fish eye.
- Good dispersibility and stability on ageing in paint systems.

APPLICATIONS

DISPARLON JXL-621 can be used for all solvent based systems and it is especially recommended for Wood, Architectural, PCM and industrial top coatings such as Alkyd melamine, Acrylic melamine, Acrylic urethane.

INCORPORATION

Recommended levels : 0.2 \sim 1.5 % by weight on total formulation.

Method: Post addition on High speed dissolver is recommended.

TYPICAL PROPERTIES

Appearance: Colorless to light yellow liquid

Active matter: 20% by wt.

Density: $0.91 \text{g/cm}^3 (25^{\circ}\text{C})$ Solvent: n-Butyl acetate



NO.5 Jinfa Road, Jinxi Town, Kunshan City, Jiangsu Province, China Zip: 215300 Tel: (86)-512-57236788