

*Additives for coatings and printing inks*  
**DISPARLON<sup>®</sup>**

Nov. 2, 2016

**DISPARLON<sup>®</sup> JXL-623**  
(Slipping/Leveling agent)

**DISPARLON JXL-623** is a silicone based slip/leveling agent. **DISPARLON JXL-623** has excellent compatibility to coatings without haze and improves slipping, scratch resistance, anti-blocking properties. It also prevents cratering, cissing and pin-hole that come from contamination taking full advantage of excellent leveling property.

**ADVANTAGES**

- Good leveling & DOI.
- Prevent crater & fish eye.
- Good dispersibility and stability on ageing in paint systems.

**APPLICATIONS**

**DISPARLON JXL-623** can be used for all solvent based systems and it is especially recommended for Wood, Architectural and industrial top coatings such as Alkyd melamine, Acrylic melamine, Acrylic urethane.

**INCORPORATION**

Recommended levels : 0.1 ~ 1.5 % by wt on total formulation.  
Method : Post addition on High speed dissolver is recommended.

**TYPICAL PROPERTIES**

Appearance : Colorless to light yellow liquid  
Active matter : 20 % by wt.  
Density : 0.91 g/cm<sup>3</sup> (25°C)  
Solvent : n-Butyl acetate



**楠本化工(昆山)有限公司**

*Kusumoto Chemicals (Kunshan) Co., Ltd.*

NO.5 Jinfa Road, Jinxi Town, Kunshan City, Jiangsu Province, China  
Zip:215300 Tel.:(86)-512-57236788