

*Additives for coatings and printing inks*  
**DISPARLON<sup>®</sup>**

Apr. 2012

**DISPARLON<sup>®</sup> L-1980-50S**

(Leveling/Flow agent)

**DISPARLON L-1980-50S** is silicone-free, non-ionic high molecular weight surface active agents. This is 50 % solids, chemically stable and have excellent dispersibility in a wide range of paint systems. This product is utilized in the advanced paint technologies including high-solids coatings and UV cured systems as surface modifiers. Especially effective in Epoxy systems.

**ADVANTAGES**

- Improve leveling and prevent pinholes.
- Improve film gloss by promoting pigment wetting, resulting in good dispersion.
- Act as defoamer.
- Have little affect on physical properties of the film such as recoatability.
- Excellent dispersibility allows post addition.

**APPLICATIONS**

**L-1980-50S** can be used in almost all type of baking high-solids coatings, thermosetting, UV curing systems, non-solvent coatings as well as conventional baking solvent based coatings and Unsaturated polyester coatings, particularly high-solids Polyester/melamine and Acrylic/melamine coatings for automotive.

**INCORPORATION**

Additive level: 0.2 ~1.5 % by wt. of finished paint.

Method: Post-addition on high speed dissolver is recommended

**TYPICAL PROPERTIES**

Appearance .....	Colorless to light yellow liquid
Non-volatile matter .....	50 % by wt.
Density .....	0.95 g/cm <sup>3</sup>
Solvent .....	Solvent naphtha/Butyl acetate



**楠本化工(昆山)有限公司**

*Kusumoto Chemicals (Kunshan) Co., Ltd.*

NO.5 Jinfa Road, Jinxi Town, Kunshan City, Jiangsu Province, China

Zip: 215300 Tel: (86)-512-57236788