

Additives for coatings and printing inks

DISPARLON

July 2018

DISPARLON SPX-44

(Defoaming agent for coatings and inks)

DISPARLON SPX-44 is a silicone defoamer for ambient cure coatings and printing inks.

ADVANTAGES

- Strong defoaming property.
- Effective in a wide range of coating and ink systems.
- No influence on coating clarity.
- Can be used with thixotropic agents.
- Aromatic-free.

APPLICATIONS

DISPARLON SPX-44 can be used in various ambient cure systems. SPX-44 is especially suitable for epoxy coatings, urethane coatings, unsaturated polyester coatings and printing inks.

INCORPORATION

Additive level : 0.2 - 1.0 % by weight on total formulation.
Method : Post-addition is recommended.

TYPICAL PROPERTIES

Appearance	Clear to light yellow liquid
Active component	1%
Solvent	Ethyl acetate

STORAGE

Storage of this product in soft-glass bottles is not recommended since the active matter may decompose under basic conditions.



Kusumoto Chemicals, Ltd.

11-13, UCHIKANDA 1-CHOME, CHIYODA-KU, TOKYO JAPAN

(TEL) 81-3-3292-8685 (FAX) 81-3-3295-6079

The information on use is based on data which are believed reliable, but any recommendation or suggestion made are without guarantee or warranty, since the conditions of use are outside our control. All products are sold on the conditions that purchasers shall make their own tests to determine the suitability of such products for their purpose and that all risks are assumed by user. We disclaim any responsibility for damages resulting from careless or improper handling or use. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license. See SDS for safety handling before to use.

© 2012 All Rights Reserved By Kusumoto Chemicals, Ltd.