

DISPARLON

October 2018

DISPARLON OX-60

(Defoaming / Anti-popping agent)

DISPARLON OX-60 is a surface control agent based on an acrylic polymer. It can work not only as defoamer in a variety of solvent based industrial coatings, but also prevent popping associated with baking. These properties make it possible to obtain thicker film in one application allowing an efficient coating operation.

ADVANTAGES

- Effective in eliminating foams and popping with industrial baking enamels.
- Easy to disperse in paint systems and long retained effects.
- Combination use with leveling agent will produce a film with high quality surface by way of further improved leveling.

APPLICATIONS

In solvent based industrial paints, particularly Alkyd melamine, Oil-free polyester melamine, Acrylic / Melamine, Acrylic / Urethane, systems etc..

INCORPORATION

Additive levels : 0.2 ~ 1.0 % by weight on total formulation.
Method : Post-addition on high-speed dissolver is recommended.

TYPICAL PROPERTIES

Appearance : Colorless to light yellow liquid
Non-volatile matter : 50 % by wt.
Density : 0.89 g/cm³ (at 20°C)
Solvent : Xylene / Toluene



Kusumoto Chemicals, Ltd.

11-13, UCHIKANDA 1-CHOME, CHIYODA-KU, TOKYO JAPAN

(TEL) 81-3-3292-8685 (FAX) 81-3-3295-6079

The information on use is based on data which are believed reliable, but any recommendation or suggestion made are without guarantee or warranty, since the conditions of use are outside our control. All products are sold on the conditions that purchasers shall make their own tests to determine the suitability of such products for their purpose and that all risks are assumed by user. We disclaim any responsibility for damages resulting from careless or improper handling or use. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license. See SDS for safety handling before to use.

© 2007 All Rights Reserved By Kusumoto Chemicals, Ltd.