

DISPARLON

March 2019

DISPARLON OX-710

(Defoaming/Leveling agent)

DISPARLON OX-710 is a defoaming/leveling agent based on polyacrylate.
OX-710 is effective for high viscosity systems such as Non-solvent coatings and Floor coatings.

ADVANTAGES

- Strong defoaming/leveling
- Prevents pinholes and crater
- Easy incorporation

APPLICATIONS

OX-710 is effective for ambient cured systems such as Alkyds, Acrylics, Urethanes, Epoxys etc.
The product is recommended for high viscosity Floor coatings and Water proofings.

INCORPORATION

Additive levels: 0.2 ~ 0.8 % by weight of final formulation
Method: Post addition on high speed dissolver

TYPICAL PROPERTIES

Appearance Clear to light yellow liquid
Non-volatile matter 50 % by wt.
Density 0.9 g/cm³
Solvent Xylene



Kusumoto Chemicals, Ltd.

11-13, UCHIKANDA 1-CHOME, CHIYODA-KU, TOKYO JAPAN

(TEL) 81-3-3292-8685 (FAX) 81-3-3295-6079

The information on use is based on data which are believed reliable, but any recommendation or suggestion made are without guarantee or warranty, since the conditions of use are outside our control. All products are sold on the conditions that purchasers shall make their own tests to determine the suitability of such products for their purpose and that all risks are assumed by user. We disclaim any responsibility for damages resulting from careless or improper handling or use. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license. See SDS for safety handling before to use.

© 2009 All Rights Reserved By Kusumoto Chemicals, Ltd.