

*Additives for coatings and printing inks*  
**DISPARLON<sup>®</sup>**

November 2022

## DISPARLON<sup>®</sup> AQ-610

(Rheology control agent for waterborne systems)

DISPARLON<sup>®</sup> AQ-610 is a rheology control agent composed of a polyamide. DISPARLON<sup>®</sup> AQ-610 forms a network structure by interacting with paint components in a coating system, prevents settling and hard caking, and improves pigment orientation. Unlike general waterborne thickeners, DISPARLON<sup>®</sup> AQ-610 can provide high thixotropic property without excess viscosity increasing.

### ADVANTAGES

- Excellent anti-settling property
- Imparts high thixotropic property without excess viscosity increasing
- Easy incorporation

### APPLICATIONS

DISPARLON<sup>®</sup> AQ-610 can be used in a wide range of waterborne coating systems, and is especially suitable for emulsion coatings and dispersion coatings.

### INCORPORATION

- Additive levels : 1.0 ~ 4.0 wt% on total formulation.  
Method : Can be added at each production stage. Post-addition at a final production stage with a dissolver is recommended.  
Keep temperature from a room temperature up to 40°C during dispersing.

### TYPICAL PROPERTIES

Appearance	Yellow paste
Active matter	15 %
Amine	N, N-dimethylethanolamine
Solvent	Water / Propylene glycol monobutyl ether
Acid value	14.0

### STORAGE

- Keep from freezing. Freezing causes severe degradation of quality and performance.
- Do not heat. Store below 40°C. Heating causes degradation of quality and performance.

### CAUTION

Due to the nature of this product, the solvent might ooze out from the paste to its surface over time. This doesn't affect its original properties. Please stir the content gently to make it uniform before use. Hand stirring is recommended because strong stirring with dissolver and addition of heat will result in degradation of its properties.



*Kusumoto Chemicals, Ltd.*

11-13, UCHIKANDA 1-CHOME, CHIYODA-KU, TOKYO JAPAN

(TEL) 81-3-3292-8685 (FAX) 81-3-3295-6079

The information on use is based on data which are believed reliable, but any recommendation or suggestion made are without guarantee or warranty, since the conditions of use are outside our control. All products are sold on the conditions that purchasers shall make their own tests to determine the suitability of such products for their purpose and that all risks are assumed by user. We disclaim any responsibility for damages resulting from careless or improper handling or use. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license. See SDS for safety handling before to use.

© 2008-2022 All Rights Reserved By Kusumoto Chemicals, Ltd.