

October 2022

# DISPARLON® SPX-20A

## (Anti-popping/defoaming agent)

**DISPARLON® SPX-20A** is a defoaming/anti-popping agent mainly composed of vinyl polymers and is suitable for high-viscosity/high-thickness ambient cure paints such as flooring and waterproofing materials. It also exhibits excellent anti-popping property for industrial baking paints.

### **ADVANTAGES:**

- Anti-popping / defoaming properties.
- Excellent leveling property / prevent benardo cells.
- Silicone free / excellent recoating property

### **APPLICATIONS**

**DISPARLON® SPX-20A** is suitable for high-viscosity, high-thickness ambient cured coatings (solvent-free epoxy, urethane, etc.) such as floor coatings or waterproofing, also general industrial baking paints (alkyd melamine, acrylic melamine, polyester melamine, etc.).

### **INCORPORATION**

Additive levels:0.1 ~ 1.5 % by weight in total paint formulation.Optimal levels are determined through prior laboratory tests.

Method: Post addition is recommended, it is also possible to add at any stage of the paint manufacturing process.

### **TYPICAL PROPERTIES**

(The following figures are typical properties, not to be used for specification.)

Appearance	Clear to light yellow liquid
Non-volatile	20% by wt.
Solvent	Solvent naphtha / n-Butyl acetate



The information on use is based on data which are believed reliable, but any recommendation or suggestion made are without guarantee or warranty, since the conditions of use are outside our control. All products are sold on the conditions that purchasers shall make their own tests to determine the suitability of such products for their purpose and that all risks are assumed by user. We disclaim any responsibility for damages resulting from careless or improper handling or use. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license. See SDS for safety handling before to use. © 2022 All Rights Reserved By Kusumoto Chemicals, Ltd.