

Additives for coatings and printing inks
DISPARLON[®]

February 2024

DISPARLON[®] SPD-202SS

(Wetting / dispersing agent)

DISPARLON[®] SPD-202SS is a pigment wetting/dispersing agent composed of an amine salt of a polyester acid amide. DISPARLON[®] SPD-202SS wets and deflocculates pigments, reduces viscosity, and improves color strength, gloss, hiding power, and DOI. DISPARLON[®] SPD-202SS is especially effective for organic pigments.

ADVANTAGES

- Excellent pigment wetting, dispersing, and viscosity reduction properties
- Shorten dispersing time
- Improves gloss, DOI, color strength and hiding power

APPLICATIONS

DISPARLON[®] SPD-202SS is especially effective for dispersing of organic pigments.

DISPARLON[®] SPD-202SS can be used for various coating systems such as industrial coatings, plastic coatings and various gravure printing inks.

INCORPORATION

- Additive levels : 60 – 150 wt% for organic pigments
15 – 150 wt% for carbon black
3 – 30 wt% for inorganic pigments
- Method : Addition at a grinding/dispersing stage is recommended.

TYPICAL PROPERTIES

(The following figures are typical properties, not to be used for specification.)

Appearance	Light yellow to amber liquid
Non-volatile matter	30 %
Acid value	8
Amine value	4
Solvent	Xylene / 2-phenoxyethanol

STORAGE

- Store at 15 – 35 deg.C. Precipitation or solidification may occur at low temperature. In this case, heat at 50 deg.C or less for more than one day and stir well before use.



Kusumoto Chemicals, Ltd.

11-13, UCHIKANDA 1-CHOME, CHIYODA-KU, TOKYO JAPAN

(TEL) 81-3-3292-8685 (FAX) 81-3-3295-6079

The information on use is based on data which are believed reliable, but any recommendation or suggestion made are without guarantee or warranty, since the conditions of use are outside our control. All products are sold on the conditions that purchasers shall make their own tests to determine the suitability of such products for their purpose and that all risks are assumed by user. We disclaim any responsibility for damages resulting from careless or improper handling or use. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license. See SDS for safety handling before to use.

© 2013 – 2024 All Rights Reserved By Kusumoto Chemicals, Ltd.